

TECRA 500CDT Product Specifications

500CDT:1.3 Billion Bytes: PA1221U-T2A

PROCESSOR

Intel Pentium® 120Mhz (2.9v/3.3v) w/VRT	Yes
External data bus width	64 bit
External data/address bus speed	60 MHz
Integrated Coprocessor	Yes
Processor Cache	16KB: (8KB code; 8KB data)

LEVEL 2 (L2) CACHE

Data Bus Width	64 bit
Data Bus Speed	60 MHz
DATA RAM:	Yes
1 Mbit Pipelined Burst Synchronous SRAM	(32K x 32bit, 3.3V) x 2
Access Time	8 ns
TAG-RAM:	Yes
256Kbit Asynchronous SRAM	(32K x 8bit, 3.3V) x 1
Access Time	14 ns

SYSTEM ARCHITECTURE (All models)

PCI BUS: (32-bit, 30 MHz)	Connecting Devices: PC Card Slots, Expansion Bus, Graphics Controller
ISA BUS: 16-bit, 8 MHz	Connecting Devices: BIOS, FDD, HDD, CD-ROM, Sound chip, KBC

MEMORY: 16Mbit EDO DRAM, 3.3V

Standard	16 MB
Maximum	144 MB
Speed	60ns
Hyper Page mode memory access	Yes
Data width	64 bit
BIOS (256KB FLASH EPROM, 150ns, 5V)	Yes
PnP 1.0a SUPPORT	Yes

DISPLAY

Type	TFT Active Matrix Color
Size	12.1" (9.68"W x 7.26"H)
Dot Pitch	.30mm x .30mm
Contrast Ratio	100:1 (min)

VIDEO

Memory: 4Mbit EDO DRAM, 5V	2 MB
Speed	50ns
Hyper Page mode support	Yes
Controller Chip	C&T HIQV32 (CT65550)
PCI Bus Architecture w/burst mode	Yes: 32-bit, 30 MHz
Graphics Accelerator:	Yes
64-bit BitBLT, LINEdraw, H/W Cursor	Yes
Video Accelerator:	Yes
YUV-to-RGB color space conversion	Yes
Zoomed Video Port Support	Yes
DirectVideo support	Yes:w/Game SDK driver fr/Microsoft
Color Palette	16.7M colors
Internal Resolution	800 x 600 x 16.7M/16.7M colors
Smaller Image	640 x 480 x 16.7M/16.7M colors
Virtual Display Mode	1024 x 768 x 64K/64K colors
	1280 x 1024 x 256/256K colors
External Resolution	<u>Colors/Palette</u>
640 x 480	16.7M colors/16.7M colors
800 x 600	16.7M colors/16.7M colors
1024 x 768	64K colors/64K
1280 x 1024	256 colors/256K

Refresh Rate @ 1024x768/ 64k colors Non-Interlaced¹ Vert.: 60Hz; Hor.: 48.5kHz

1. Refresh Rate @ 1024x768/ 256 colors Non-Interlaced : Vert.: 85 Hz; Hor.: 68.8 kHz

TECRA 500CDT Product Specifications

500CDT:1.3 Billion Bytes: PA1221U-T2A

STORAGE

Removeable HDD (2.5" Enhanced IDE) 1.3 billion bytes=1.26GB (13msec)

SELECT BAY DEVICES

Modular FDD (3.5" 1.44MB)

FDD Dimensions

FDD Weight

Simultaneous FDD & CD-ROM Support³

FDD Adapter Dimensions

FDD Adapter Weight

Modular HDD (2.5" Enhanced IDE)

Capacity

Modular CD-ROM: Toshiba XM-1402B

5.25" 6x-speed

Weight

Interface

Random Access Time

Sustained Transfer Rate

Supported Disc formats

Included/Swappable with CD-ROM

4.57"L x 3.8"W x .59"H

Weight: .29 lbs

Yes: External FDD adapter included

7.0"L x 5.5"W

.25 lbs

Optional/Swappable with FDD

1.3 billion bytes=1.26GB (13msec)

Installed/Swappable with FDD

.4 lbs

.ATAPI (Enhanced IDE)

190 ms

1,026 KB/sec

CD-DA, CD-ROM, CD-ROM XA, CD-Bridge (Photo-CD, Video-CD),

CD-I, CD-I Ready, CD-G, Multisession (Photo-CD, CD-Plus)

KEYBOARD

82 keys, 3mm Travel Yes

12 dedicated function keys Yes

Cursor control (8 Keys, Inverted "T") Yes

Numeric keypad (Integrated Overlay) Yes

Integrated Pointing Device AccuPoint™

EXPANSION SLOTS

Two Stacked PC Card Slot² Yes: CardBus & ZV Card Ready

32-bit, 3.3V PC CardBus Support Yes

16-bit, 5.0V PC Card Support Yes

Internal Memory Slot (One only) Yes

EXPANSION PORTS

One RJ-11 port for internal modem (supplied) Yes

One 9-Pin Serial (16550 UART compliant) Yes

One 25-Pin Parallel (8 bit ECP) Yes

One 15-Pin RGB (SVGA video) Yes

Fast Infrared ports (Front and Back) Yes: IrDA 1.1:4Mbps compatible

One (PS/2) 101 Keyboard/Mouse port Yes

One External Floppy Drive port Yes

Microphone (3.5mm mini jack, monoaural) Yes

Headphone (3.5mm mini jack, stereo) Yes

Line-in (3.5mm mini jack, stereo, 2V rms) Yes

Line-out (3.5mm mini jack, stereo, 0.7V rms) Yes

Noteworthy security lock port Yes

INTERNAL MODEM (All Models) 28.8 /14.4 Kbps Data/Fax/Voice modem

Data support

Protocols supported

Error correction

Data compression

Fax support

Protocols supported

Fax class

Supported Functions

Bell-103/212A, CCITT-V.21/V.22, V.32, V.32bis, V.34

MNP 1-4

MNP 5, CCITT V.42 bis

V.21 ch2, V.27 ter, V.29, V.17

1

Speaker phone, Telephony Answering Machine, Ring Wake-up Resume

Incoming Call Discrimination, Caller ID

² Holds two - 5mm PC Cards Type II or one - 10.5mm PC Card Type III. ³ External FDD adapter is included w/the purchase of CD-ROM kit (PA2657U).

TECRA 500CDT Product Specifications

		500CDT: 1.3 Billion Bytes: PA1221U-T2A
Desk Station V Plus (Optional)		Part# PA2710U
(2) Full length 32-bit PCI/16-bit ISA slots		Yes
(1) Half Length 32-bit PCI slot		Yes
(2) Type III PC Card slots		Yes
Built-in SCSI II		Yes
5.25" half height drive bay		Yes
Select Bay for Modular FDD, HDD, CD-ROM		Yes
Designed for Windows 95 and PNP		Yes
Hot Docking Support		Yes
NoteDock II™ Port Replicator (Optional)		Part# PA2713U
Two Type III CardBus ready PC Card slots		Yes: each slot supports one card
Supported Interfaces		Serial, parallel, PS/2 keyboard, PS/2 mouse, DC in, SVGA monitor, lock slot , joystick/MIDI, audio line-in, line-out, headphone, microphone
POWER		
Autosensing Internal AC Power Supply		Yes
Input (Voltage/Frequency)		100-240V; 50-60Hz
Output (Voltage/Amps)		15 VDC; 2A (max)
Power Output (Watts)		30W
Battery Type: Li-Ion (10.8V, 3600mAH)		Yes: Part# PA2490UR
Battery Life: (Full Power/Low Power)		2+ hrs.
Recharge Time (Computer Off/On)		2-3 hrs.(Off) /5-8 hrs.(On)
MaxTime® Power Management		Yes
SOUND SYSTEM (All Models)		
Chipsets:		Crystal Semiconductor CS4232, Yamaha OPL3 (YMF262), Yamaha D/A converter (YAC512)
16 bit stereo audio playback/record		Yes
Full duplex function		Yes
Sound formats supported:		SoundBlaster Pro™, .WAV, MIDI, Zoomed video port audio (stereo), CardBus audio (monaural), CD-ROM audio
DirectSound support		Yes: with Windows 95 Game SDK driver from Microsoft
Speaker system:		Two top-mounted stereo speakers (28mm, 8 Ω)
DIMENSIONS		11.77"W x 9.25"D x 2.28"H
WEIGHT (includes .86 lbs. battery)		8.0 lbs.
BUNDLED SOFTWARE (All Models)		<i>User selectable</i> Windows® 95 <i>or</i> Windows® for Workgroups 3.11 and MS-DOS 6.22® w/Special Enhancements; Intel Indeo Video™; Synchro Multimedia Connect Communications utilities; Sony Music Screeners™ screen saver; Mediamatics MPEG ARCADE Player™, America Online®, CompuServe®, Netscape Navigator™, magiCDisc™, Dow Jones Personal Journal™, Fn-esse™, Hypertext online documentation
SECURITY (All Models)		Lock slot, power-on & HDD password, screen blank, keyboard lock
WARRANTY		3 YR Parts & Labor
ENVIRONMENTAL SPECIFICATIONS		
Temperature:	Operating	41°F (5°C) to 95°F (35°C)
	Non-operating	-4°F (-20°C) to 149° (65°C)
	Thermal Gradient	20° C per hour (max.)
Relative Humidity:	Operating	20% to 80% non-condensing
	Non-operating	10% to 90% non-condensing
Altitude:	Operating	-197 to 9,843ft. (-60 to 3000m)
	Non-operating	-197 to 32,808ft. (-60 to 10,000m)
Shock:	Operating	10G; 1.5G w/CD-ROM installed
	Non-operating	60G; 50G w/CD-ROM installed
Vibration:	Operating	0.5G; 0.25G w/CD-ROM installed
	Non-operating	1G; 1G w/CD-ROM installed